

V5°α / V5°



Compatibility



All Low Voltage Series



Sunny Island Storage Series



LXP Hybrid Series



Multi/Quattro Series



Any-grid PSW-H 48V Series



RHI 48ES Series



RLNA Series



SPH/SPF US Series



Infinisolar LV Series



ELS-5K PCS

Features



Remote Monitoring and Upgrading



Higher Charge/Discharge Rate



Wider Operation Temperature



Higher Energy Density



Greater scalability

10 Years Warranty



UN38.3



CEC SGIP

V5°/ V5°α Specs

Electrical

Nominal Voltage	51.2V
Voltage Range	47.5V~57.6V
Nominal Capacity	100Ah
Nominal Energy	5.12kWh
Recommended Charge/ Discharge Current ^[1]	75A
Max Continuous Charge/ Discharge Current ^[2]	100A
Peak Charge/Discharge Current	101A~120A(3min) ; 121A~180A(15sec)
Connection Options	V5°: PHOENIX M6 Bolt V5°α: Amphenol SurLok Plus 8.0mm

[1], [2]: The recommended and Max continuous charge and discharge current is for a battery cell temperature within 10°C~40°C(50°F~104°F) to consider. It will result in a derating on current if out of the temperature range.

General

Chemistry	LFP
Communication Protocol	CAN / RS485
Dimensions (L*W*H)	440 * 530 * 140 mm (3.2U) / 17.3 * 20.9 * 5.5 inch (3.2U)
Weight	44 kg / 97 lbs
Ambient Temperature	-10°C~55°C / 14°F~131°F
Round-Trip Efficiency	≥95%
Cycle Life ^[3]	≥6000cycle
Warranty	10 Years

[3]: Test conditions 0.2C Charging/Discharging, @25°C(77°F), 80% DOD.

Add-on Functionalities

WIFI Connection	Remote monitoring and upgrade
Heating Pad	Around 10°C / h / Around 18°F / h
Scalability	14 pcs (71.68kWh) in a group 6 groups (430.08kWh) in a system w / a Hub

Certifications (On-going)

UL9540 Ed.2 (2020), UL9540A, UL1973, CEC, SGIP, CE, IEC62619, UN38.3